

United States Patent [19]**Natsuume**[11] **4,042,407**[45] **Aug. 16, 1977**[54] **HYDRAULIC COMPOSITION**[75] **Inventor:** Tadao Natsuume, Yokosuka, Japan[73] **Assignee:** Nippon Zeon Co., Ltd., Tokyo, Japan[21] **Appl. No.:** 596,150[22] **Filed:** July 15, 1975[30] **Foreign Application Priority Data**

July 17, 1974 Japan 49-81870

Mar. 4, 1975 Japan 50-26197

[51] **Int. Cl.²** **C04B 7/35**[52] **U.S. Cl.** **106/90; 106/97;**
106/314[58] **Field of Search** 106/90, 97, 98, 314,
106/315; 260/29.6 S

[56]

References Cited**U.S. PATENT DOCUMENTS**

2,790,724	4/1957	Bergman	106/90
3,817,767	6/1974	Bozer et al.	106/98
3,923,717	12/1975	Lalk et al.	106/314

Primary Examiner—J. Poer*Attorney, Agent, or Firm*—Sherman & Shalloway

[57]

ABSTRACT

A hydraulic composition comprising 100 parts by weight of a hydraulic substance and as a water-reducing admixture 0.01–2.0 parts by weight of a water-soluble polymer, said polymer being selected from the group consisting of a specific water-soluble olefin-ethylenically unsaturated dicarboxylic acid salt copolymer and a specific derivative of said copolymer.

22 Claims, No Drawings